


## LED WALL PACKS - LS Series

### Product Description

The LS Series led wall pack has a same beautiful look as traditional wall packs, but with over 120-130lm/W light efficiency, best aluminum heat dissipation sink. equipped with long lasting driver which last 50000hrs, ideal for replacing old wall packs 100-600W.

### Application

Outdoor building, Wall area, General area and Security lighting etc



### Electric Characteristic

Specification/Model	LS-WP41W	LS-WP60W	LS-WP80W	LS-WP100W	LS-WP120W	LS-WP150W
LED Chips	Philip3030					
Input power	41W	60W	80W	100W	120W	150W
Lumens output	4920-5330LM	7200-7800LM	9600-1040LM	12000-13000LM	14400-15600LM	18000-19500LM
Efficiency	120-130LM/W	120-130LM/W	120-130LM/W	120-130LM/W	120-130LM/W	120-130LM/W
CRI	75Ra					
Color Temperature	3000/4000K/5000K					
Input voltage	100-277V UL Driver					
Lighting beam	120D					
Power Factor	0.9					
Total Harmonic Distortion	13.4%					
lamps efficiency	90%					
Certificates	ETL, CETL, DLC					
Equivalent	100-150W MH/HPS	150-200W MH/HPS	250-300W MH/HPS	300-350W MH/HPS	350-450W MH/HPS	450-600W MH/HPS


## LED WALL PACKS - LS Series

### Ordering Information

Example: LS-WP41W-30K-N-T

Product	Power	Replacement	Color Temperature	Photocell	Furnish
LS-WP41W(5000K)	41W	100-150W MH/HPS	30K=3000K 40K=4000K 50K=5000K	N not photocell Y yes photocell	WP=Wall Pack
LS-WP60W(5000K)	60W	150-200W MH/HPS			
LS-WP80W(5000K)	80W	250-300W MH/HPS			
LS-WP100W(5000K)	100W	300-350W MH/HPS			
LS-WP120W(5000K)	120W	350-400W MH/HPS			
LS-WP150W(5000K)	150W	450-600W MH/HPS			

### Photometri




### Projected LED Lumen Maintenance

Operating hours	0	25000	50000
Lumen maintenance factor	1	0.91	0.8

Data references the extrapolated performance projections for the WALLPACK LED platform in a 25°C ambient, based on 10,000 hours of LED testing (tested per IESNA LM-80-08 and projected per IESNA TM-21-11)

### Dimensions:



### After sale Service:

The product refers to electricians' knowledge. Please don't disassemble it by yourself. If any quality problem happens, please contact the factory for warranty details.  
NOTE: Actual performance may differ as a result of end-user environment and application. All values are without notice.