

Wattages: 95W, 120W, 150W, 200W



WISDOM LED Gas Station Canopy Light series can be widely used in indoor or outdoor lighting (wet location), excellent for gas station, museums, art galleries, shopping malls, parking garage, buildings, lawn, and many more applications.



### FEATURES

- LED high luminous efficiency and long working life.
- High efficiency LED Driver, the wide range input voltage AC120-277V.
- Die-cast aluminum cooling design, high quality and better cooling for LED  $T_j < 85^{\circ}\text{C}$ .
- Excellent optics design, greatly improve the light utilization and evenness.
- Motion sensor control available (Optional)

### CONTROLS




**BRI810-B-M8**  
Mounts in an outdoor lighting fixture and provides multi-level control based on motion and/or daylight contribution




**RC**  
Remote Controller

SPECIFICATION				
WATTAGE	95W	120W	150W	200W
LUMEN	12721 lm	16086 lm	21250 lm	28390 lm
EFFICACY	130 lm/W	130 lm/W	140 lm/W	140 lm/W
CCT	4000K, 5000K			
CRI	70			
INPUT VOLTAGE	AC120-277V			
BEAM ANGLE	111°	109°		105°
POWER FACTOR	0.95		0.98	
DRIVER EFFICACY	90%		93%	
DIMMING	1-10V dimming			
LIFE SPAN	over 50,000 hrs			
WORKING TEMPERATURE	-22°F ~ 113°F			
STORAGE TEMPERATURE	-40°F ~ 176°F			
OUTDOOR RATING	Wet location			
CABLE	Input Connect (27.56 inch)			
WARRANTY	5 year limited			

**Wattages: 95W, 120W, 150W, 200W**



### DIMENSION



<b>WATTAGE</b>	95W, 120W
<b>GR. WEIGHT</b>	9.87 lbs
<b>BOX DIMENSION</b>	17.13" x 17.13" x 4.13"

<b>WATTAGE</b>	150W, 200W
<b>GR. WEIGHT</b>	16.06 /14.78 lbs
<b>BOX DIMENSION</b>	18.7" x 18.7" x 4.92"

### ORDERING INFORMATION

EXAMPLE:

**WSD-CP95W27-XXK-Z[D, W, B, S]-E[BLANK, M]**

WSD	CP	95W	27	XXK	Z	E
COMPANY	PRODUCT	WATTAGE	VOLTAGE	CCT	FINISH	CONTROL
WSD LED INC	CP (Gas Station Canopy)	95W - (95W) 12W - (120W) 15W - (150W) 20W - (200W)	27 (AC120-277V)	40K - (4000K) 50K - (5000K)	D - (Dark Bronze) W - (White) B - (Black) S - (Silver)	M - (Motion Sensor)


Wattages: 95W, 120W, 150W, 200W

### PHOTOMETRICS

For complete IES files, please visit our website.


#### WSD-CP95W27-50K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE(50%):107,7 DEG

CO PLANE ISOLUX DIAGRAM (UNIT:lx)




#### WSD-CP120W27-50K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE(50%):108,2 DEG

CO PLANE ISOLUX DIAGRAM (UNIT:lx)




#### WSD-CP150W27-50K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE(50%):103,6 DEG

CO PLANE ISOLUX DIAGRAM (UNIT:lx)



#### WSD-CP200W27-50K

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE(50%):102,8 DEG

CO PLANE ISOLUX DIAGRAM (UNIT:lx)

