


Wattages: 35W,50W,60W;100W,150W,200W;240W,350W,450W



240-450W

100-200W

35-60W

The SELECTABLE LED FLOOD Lighting Series can be widely used for Outdoor Excellent for Parking Lots, Pedestrian Walkways, Roadways, Tennis Courts, Basketball Courts, Stadiums, Arenas, Schools, Residential Areas and many other applications.



Features:

- Optical design, greatly improved the light utilization and evenness
- High efficiency LED Driver, voltage AC120-277V
- Cast Aluminum design, better cooling, light quality, LED Tj <85°C
- 0-10V dimming standard
- CCT:3000-5000K
- 5 years manufacturer warranty
- Compatible with most Lutron and Leviton dimmers


Packaging information:

- ❖ **WSD-FL3556W27-345K-D-K-P**
Inner Box:263MMX204MMX66MM (10.35" X8.03" X2.60")
Outer Box:415MMX207MMX269MM(6Pcs/CTN) (16.34" X8.15" X10.59")
- ❖ **WSD-FL101520W27-345K-D-P**
507MMX414MMX138MM(1Pcs/CTN) (19.96" X16.30" X5.43")
- ❖ **WSD-FL243545W27-345K-D-P**
710MMX615MMX159MM(1Pcs/CTN) (27.96" X24.21" X6.26")

SPECIFICATION									
TYPE	WSD-FL3556W27-345K-D-K-P			WSD-FL101520W27-345K-D-P			WSD-FL243545W27-345K-D-P		
WATTAGE	35W	50W	60W	100W	150W	200W	240W	350W	450W
LUMEN	5320 lm	7400 lm	8760 lm	15600 lm	22950 lm	30000 lm	37440 lm	53200 lm	67050 lm
CCT	3000K/4000K/5000K								
EFFICACY	> 140 lm/W								
CRI	> 80								
INPUT VOLTAGE	AC120-277V								
LIGHTING ANGLE	118°								
FACTORY SETTINGS	60W & 4000K Light-Sensitive Opening			200W & 4000K Light-Sensitive Opening			450W & 4000K Light-Sensitive Opening		
LED TYPE	SMD2835								
PF	> 0.98								
DRIVER EFFICIENCY	> 90%								
PROTECTION LEVEL	Wet location								
LIFE TIME	> 50000 hours								
CABLE	Score,18AWG (8.66 inch)			Score,18AWG (3.94 inch)					
WARRANTY	5 year limited								

Wattages: 35W,50W,60W;100W,150W,200W;240W,350W,450W

DIMENSION:



SPECIFICATIONS:

Shell materials: Aluminum & Glass.
 Finish: Dark Bronze(Standard)
 Net weight :

35-60W:2.95(lbs)
 100-200W:12.15(lbs)
 240-450W:25.29(lbs)

Product Size:

35-60W:200mmX150mmX52mm
 7.87"X5.91"X2.05"

100-200W:341mmX253mmX87mm
 13.41"X9.97"X3.42"

240-450W:541mmX456mmX114mm
 21.29"X17.97"X4.48"

MOUNTING OPTIONS:(SOLD SEPARATELY)



NAME	Knuckle
TYPE	WSD-FLK-Bracket-35W-60W
FINISH	Bronze
USE	Available For Low Wattages (35W-60W)
FACTORY STANDARD	Knuckle



NAME	Slip Fitter
TYPE	WSD-FLSF-Bracket-100W-450W
FINISH	Bronze
USE	Available For High Wattages (100W-450W)
FACTORY STANDARD	NO




NAME	U-Bracket
TYPE	WSD-FLU-Bracket-30W-60W / WSD-FLU-Bracket-100W-450W
FINISH	Bronze
USE	Available For ALL Wattages (35W-450W)
FACTORY STANDARD	NO

Wattages: 35W,50W,60W;100W,150W,200W;240W,350W,450W

CONTROL MODULE:



3-Way Extreme Adjustability



The floodlights all feature 3-stage color temperature adjustment, 3-stage brightness adjustment, and the option to install additional controls over the integrated Photocell.

EPA OF AREA LIGHT:

Item	1	2 @90°	2 @120°	2 @180°	3 @90°	3 @120°	4 @90°
35-60W	0.641	1.282	1.481	1.382	1.923	1.743	2.564
100-200W	0.644	1.288	1.466	1.376	1.966	1.768	2.576
240-450W	0.677	1.354	1.495	1.371	2.031	1.965	2.708

ORDERING INFORMATION:

EXAMPLE:

WSD-FL3556W27-345K-Z[D,W,B,S]-U[K,T]-Y[Black,P]/WSD-FL101520W27-345K-Z[D,W,B,S]-U[S,T]-Y[Black,P]


WSD	FL	3556W	27	345K	Z	U	Y
COMPANY	PRODUCT	POWER	VOLTAGE	CCT	FINISH	MOUNLIGHT	CONTROL
WSD - (WSD LED INC)	FL LED FLOOD LIGHT	3556W (35W/50W/60W) 101520W (100W/150W/200W) 243545W (240W/350W/450W)	27 AC120-277V	345K 3K (3000K) 4K (4000K) 5K (5000K)	D (Dark Bronze) W (White) B (Black) S (Silvery)	S (Slip fitter) T (Trunnion) K (Knuckle)	P Photocell

Wattages: 35W,50W,60W;100W,150W,200W;240W,350W,450W

CONTROL MODULE:



3-Way Extreme Adjustability



The floodlights all feature 3-stage color temperature adjustment, 3-stage brightness adjustment, and the option to install additional controls over the integrated Photocell.

EPA OF AREA LIGHT:

Item							
	1	2 @90°	2 @120°	2 @180°	3 @90°	3 @120°	4 @90°
35-60W	0.641	1.282	1.481	1.382	1.923	1.743	2.564
100-200W	0.644	1.288	1.466	1.376	1.966	1.768	2.576
240-450W	0.677	1.354	1.495	1.371	2.031	1.965	2.708

ORDERING INFORMATION:

EXAMPLE:

WSD-FL3556W27-345K-Z[D,W,B,S]-U[K,T]-Y[Black,P]/WSD-FL101520W27-345K-Z[D,W,B,S]-U[S,T]-Y[Black,P]


WSD	FL	3556W	27	345K	Z	U	Y
COMPANY	PRODUCT	POWER	VOLTAGE	CCT	FINISH	MOONLIGHT	CONTROL
WSD - (WSD LED INC)	FL LED FLOOD LIGHT	3556W (35W/50W/60W) 101520W (100W/150W/200W) 243545W (240W/350W/450W)	27 AC120-277V	345K 3K (3000K) 4K (4000K) 5K (5000K)	D (Dark Bronze) W (White) B (Black) S (Silvery)	S (Slip fitter) T (Trunnion) K (Knuckle)	P Photocell

Wattages: 35W,50W,60W;100W,150W,200W;240W,350W,450W


PHOTOMETRICS:

For complete IES files, please visit our website.

WSD-FL3556W27-345K-D-K-P (60W,4000K)



WSD-FL101520W27-345K-D-S-P (200W,4000K)



WSD-FL243545W27-345K-D-S-P (450W,4000K)

