

## SOLAR POWERED LED STREET LIGHT – RX Series Mars V 10000 Vertical



### PRODUCT OVERVIEW

Solar street and area light, made in USA. Built with premium components and engineered for durability, our fixtures deliver dependable performance, lower energy costs, and long-lasting illumination—without relying on the grid.

### FEATURES

- **LiFePO4 Battery** – For long lifetime, 230.4Wh battery capacity, over 2000 recycle times (5 years).
- **Monocrystalline Solar Panel** – 23% efficiency 75W solar panel. Heavy duty design.
- **Mounting Arms Option** – Can be used on wall or pole.
- **Anti-Bird Spike Option** – Protects solar panel surface from bird droppings.
- **60W Vertical Solar Panel** – Strong connector for 90-degree rotation. Connects to poles from 2 3/8" to 3" diameter (can be customized)

### APPLICATIONS

- Streetlights
- Parking lot / area lights
- Pathway lighting
- Lighting where power is unavailable or unstable

### Product Description

PART#	DESCRIPTION	LED WATTAGE	SOLAR PANELS	EFFICACY	LUMEN OUTPUT
RX-MARS-SS-010--US-V	10000lm Solar Powered LED System	43W	75W/60W	230lm/W	10000lm

**SOLAR POWERED LED STREET LIGHT – RX Series Mars V 10000 Vertical**
**Specifications**

<b>MODEL#</b>		<b>RX-MARS-SS-010-US-V</b>
<b>SPECIFICATIONS</b>		
Rated Wattage		43W
Lumens		10000lm
LED Efficacy		230lm/W
CCT		3000K / 4000K / 6000K
CRI (Ra)		>70
Reported L80		>50,000hrs
LED		Phillips Chips
Beam Angle		Type III
<b>SOLAR CHARACTERISTICS</b>		
Solar Panel		18V/75W
Photovoltaic Panel		Mono-Crystalline Solar Panel
Vertical PV Panel		18V/60W
Li-on Battery		12.8V/18Ah
Working Mode		1H100% 2-3H80% 4H60% 5H-dawn 25%
Output Voltage		DC43V
*Note: This is the running time of the product when it is fully charged without any recharging. Normally the luminaires are constantly converted into electricity by absorbing sunlight every day, so the running time of this product will be longer under normal conditions.		
<b>ENVIRONMENTAL</b>		
IP Rating		IP65
Impact Rating		IK08
Operating Temperature		-20°C to 60°C
<b>MATERIALS &amp; WORKING MODE</b>		
Materials		High-transmission low-iron tempered glass, EVA, TPE
ASW 3.0 Technology		ASW 3.0 patented technology automatically reduces the output power and output current when it detects the battery is at low power, thus allowing the solar luminaire to operate for longer time on continuous rainy or cloudy days.*
*Note: Other operating modes can be customized upon request.		
<b>CONTROLS</b>		
Controller Type		MPPT controller
Motion Sensor		Microwave sensor
<b>WARRANTY &amp; CERTIFICATIONS</b>		
Warranty		3 years
Certifications		CE
<b>BATTERY</b>		
Charging Time		4-6 hours
Working Hours		40-50 hours